

BEIJING RUNBO RUNFENG AGRICULTURAL EQUIPMENT CO.LTD

Address: Economic Development Zone, Daxing District, Beijing, China

Tel: 0086-10-69229851,

Fax: 0086-10-81283982


CATALOGUE



Description: XLXS-1250 Drop hammer Ventilator				
Model:	XLXS-1250		shipment time: Within 10days	
Moter	1.1KW, 380V, 50HZ			
Q'ty/Export Carton:	1pc			
Dimension/Export	1380*1380*430mm			
G/N Weight/Export Box:	90kgs			
The product describes: BLADES ARE MADE FROM STAINLESS STEEL 201, SHUTTER ARE STAINLESS STEEL 430				
Technical data/Type	Wind Capacity	Electric Power	Dimension	Voltage
XLXS-1000	35000m ³ /h	0.75KW	1100X1100X400	380V
XLXS-1250	42000m ³ /h	1.1KW	1380X1380X430	380V
XLXS-1400	55800M ³ /h	1.5KW	1536*1536*430	380V



Description: ETXS-1250 centrifugal shutter system Ventilator				
Model:	ETXS-1250		Delivery Time: Within 7days after receiving	
Moter	1.1KW, 380V, 50HZ			
Q'ty/Export Carton:	1pc			
Dimension/Export Carton:	1380*1380*430mm			
G/N Weight/Export Box:	90/88kgs			
The product describes: BLADES ARE MADE FROM STAINLESS STEEL 201, SHUTTER ARE STAINLESS STEEL 430				
Technical data/Type	Wind Capacity	Electric Power	Dimension	Voltage
ETXS-1000	35000m ³ /h	0.75KW	1100X1100X400	380V
ETXS-1250	42000m ³ /h	1.1KW	1380X1380X430	380V
ETXS-1400	55800m ³ /h	1.5KW	1536X1536X450	380V



Description: Evaporative Cooling Pad (7090)				
specification	7090	5090		
height(mm)	1500.1800.2000		Payment Term:	L/C, T/T
thickness(mm)	100,150,200		shipment time:	Within 7days
width(mm)	600			
the height of wave(mm)	7			

Product Name**Coal -burning Heater**

Technical data	unit	XL5	XL10	XL20	XL30
Heat output	Kcal/h	50,000	100,000	200,000	300,000
Heating Supplying area	M2	300	600	1200	above 1200
heat efficiency	%	≥85	≥85	≥85	≥85
Gas temperature from chimney	℃	80-150	80-150	80-150	80-150
Power	KW	1.25	2.35	4.55	4.6
Voltage	V	380/220	380/220	380/220	380/220
Outer size	mm	1250×800×1200	1500×950×1400	2000×1200×1600	2300×1300×1900
weight	kg	750	1150	1650	2100

**Product Name****Oil-burning Heater**

Technical data	unit	XL5	XL10	XL20
Heat output	Kcal/h	50,000	100,000	200,000
Heating Supplying area	M2	300	600	1200
heat efficiency	%	≥85	≥85	≥85
Hot air temperature from pump	℃	50-80	50-80	50-80
Gas temperature from chimney	℃	120-190	120-190	120-190
heating valume	m ³ /h	7000	11000	20500
consume of fuel	kg/h	2-6	4-12	8-20
suitable fuel		0#diesel	0#diesel	0#diesel
Outer size		1200×850×1000	1500×950×1100	1700×110×1150
weight	kg	280	320	500

**Product Name****Auto-water Heater**

Technical data	unit	XL10	XL20	XL40
Heat output	Kcal/h	100,000	200,000	400,000
outlet temperature of air	℃	60-120	60-120	60-120
outlet temperature of water	℃	50-80	50-80	50-80
power	KW	2.15	3.35	3.35
Voltage	V	380/220	380/220	380/220
Outer size	mm	1500×900×1450	1600×1100×1450	1950×1200×1600
weight	kg	500	800	1400

